


SPRAY BARNIZ ACRÍLICO 1 C **B-5001**

1K B-5001 Acrylic Clearcoat



DESCRIPTION



1-component acrylic clearcoat for spot repair. It stands out for its quick drying, easy and universal application, and for its gloss, resistance to scratches, blows and weathering (UV). Suitable for painting indoor and outdoor. Repels dirt through its particularly smooth surface.

Limited resistance to petrol. Good polishing quality.

SURFACE PREPARATION



Applied directly on solvent-based two-coat basecoat, not before 30 minutes after applying the basecoat or until the film is completely matt.

USE





Shake the can for 2-3 minutes before using Spray Barniz Acrílico **B-5001**.

Apply 2 cross coats at 5 to 10-minute intervals to allow thinner flash.

Do not apply on synthetic paints.

After using, turn the can upside down and press for cleaning the nozzle.

APPLICATION 

 Shake can	2-3'
 Painting distance	20-30 cm
 Number of Coats Total thickness	2 40-50 µm
 Flash time	5-10'
 Drying Time 20°C 60°C	1h 40'
 IR Drying Time	15-20'
 Polishing	IR: 15-20' Booth: 60°C / 40' Air: 24 h
 %Gloss 60°- 60°	>80%

Can be recoated after 24 hours in the air or after forced drying.

SAFETY INSTRUCTIONS 

The use of appropriate personal protective equipment is recommended during application, to prevent the irritation of the respiratory tract, skin and eyes. For professional use only.

STORAGE 

Keep in a tightly covered container, in a dry and ventilated place, avoiding direct exposure to sunlight. Temperature above 5°C is recommended, between 15 and 30°C optimal.

CAUTION: Under no circumstances should the packaging exceed 50°C.

VOC 

The VOC content of **Barniz Acrílico 1C B-5001** Spray is a maximum of 840 g/l in compliance with European regulation 2004/42/EC IIB(E) (840) <840 g/l.

The information contained in this Technical Specification Sheet is based on the knowledge and experience of the BESA technical department, and with it it's intended to advice and inform, being the responsibility of the user to take the necessary measures to guarantee the intended purpose of the product. **FOR PROFESSIONAL USE ONLY.**
